

KYTOLA® Model 2914 Constant Flow Regulator is a sturdy, industrial constant flow regulator. It is designed to provide constant flow of medium volume liquid flows in applications where supply or back pressure varies.



Model 2914 equipped with model VL flow meter

- For liquid
- High performance
- Reliable operation
- Optional Model VL flow meter for flow rate setting and monitoring

ISO 9001:2008 ISO 14001:2004

CONSTANT FLOW REGULATOR 2914

The regulator is a membrane type differential pressure controller with a built-in needle valve for flow adjustment. It is usually supplied with Model VL variable area flow meter.

FEATURES

Two-piece stainless steel construction

Easy maintenance

Competitively priced

- **TYPICAL APPLICATIONS**
- Control of seal waters
- Control of flush waters

Batching of liquids

Water purging

OPTIONS

High ∆p model


Thread adapters

Flow meter


2914


TECHNICAL DATA

Model	2914	
Max. flow	20 L/min H₂O	
Nominal flow	14 L/min H₂O	
Max. differential pressure	12 bar (*20 bar)	
Max. static pressure	25 bar	
Pressure drop at nominal flow	3 bar	
Max. temperature	90°C (momentary 120°C)	
Body	AISI 316	•
Valve	AISI 316	
Spring	AISI 316	
Membrane	EPDM	
Seals	Nitrile	
Connections	BSP 1/2" or NPT 1/2"	0
Installation position	Any required	
Weight	1.8 kg	*Special construction on request



NOTE: Model 2914D has a small bypass flow through the regulator when the flow adjustment valve is shut to prevent damages of the membrane.





 L/min H₂O
 PERFORMANCE

 0
 0
 0
 Valve

 10
 0
 0
 0
 Valve

 0
 0
 5
 10
 Ap/bar

www.kytola.com

Kytola Instruments Oy Olli Kytölän tie 1 FI-40950 Muurame, Finland Tel. +358 20 779 0690 Fax +358 14 631 419 E-mail info@kytola.com

isc

9001=ISO 1400